## **ANASAZI** AMBROSIA





**CATEGORY** 

Panel

**PROPERTIES** 



CONTENT

100% Recycled Polyester (80% Pre-/20% Post-Consumer)/80% Recycled Polyester/20% Recycled Polyester

ADDITIONAL FINISHING AVAILABLE (CHECK FOR PRICING)

Nano-Tex

**FINISH** 

None

**WIDTH** 

66"

WEIGHT

10.4

SHOWN RAILROADED

No

DIRECTIONALITY

Yes

**ROLL LENGTH** 

60

VISUAL REPEAT

14.4, 9.6

**BREAKING STRENGTH** 

Warp: 2249.0 lbs. / Fill: 1664.0 lbs.

**SEAM SLIPPAGE** 

Warp: Ibs. / Fill: Ibs.

ABRASION RESISTANCE

Exceeds 15,000 Double Rubs (Wyzenbeek/Cotton Duck)

PILLING RESISTANCE

Class: N/A

COLORFASTNESS TO CROCKING

Dry: Class 4 min / Wet: Class 4 min

**COLORFASTNESS TO LIGHT** 

40 hours

## CLEANING

WS: Water/Solvent Cleaner - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

Additional cleaning details at www.mayerfabrics.com





