

ANASAZI AMBROSIA

156-003

MAYER FABRICS



CATEGORY

Panel

PROPERTIES



CONTENT

100% Recycled Polyester (80% Pre-/20% Post-Consumer)

ADDITIONAL FINISHING AVAILABLE (CHECK FOR PRICING)

Nano-Tex

FINISH

None

WIDTH

66"

WEIGHT

10.4

SHOWN RAILROADED

No

DIRECTIONALITY

Yes

ROLL LENGTH

60 yards

VISUAL REPEAT

14.4, 9.6

BREAKING STRENGTH

Warp: 2249.0 lbs. / Fill: 1664.0 lbs.

SEAM SLIPPAGE

Warp: lbs. / Fill: lbs.

ABRASION RESISTANCE

exceeds 15,000 Double Rubs (Wyzenbeek)s

PILLING RESISTANCE

Class: N/A

COLORFASTNESS TO CROCKING

Dry: Class 4 min / Wet: Class 4 min

COLORFASTNESS TO LIGHT

40 hours

CLEANING

WS: Water/Solvent Cleaner - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

[Additional cleaning details at www.mayerfabrics.com](http://www.mayerfabrics.com)

