

# SEQUEL CYAN

312-044

# MAYER FABRICS



**CATEGORY**  
Seating/Panel

**PROPERTIES**

**CONTENT**  
100% Polyester

**ADDITIONAL FINISHING AVAILABLE  
(CHECK FOR PRICING)**  
Nano-Tex, NanoGuard

**FINISH**  
Nanotex®

**WIDTH**  
54"

**WEIGHT**  
13

**SHOWN RAILROADED**  
No

**DIRECTIONALITY**  
Yes

**ROLL LENGTH**  
60

**VISUAL REPEAT**  
None

**BREAKING STRENGTH**  
Warp: 267.0 lbs. / Fill: 271.0 lbs.

**SEAM SLIPPAGE**  
Warp: 35.0 lbs. / Fill: 47.0 lbs.

**ABRASION RESISTANCE**  
Passes 288,000 Double Rubs\* (Wyzenbeek/Cotton Duck) \*  
\* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

**PILLING RESISTANCE**  
Class: 4

**COLORFASTNESS TO CROCKING**  
Dry: Class 4 / Wet: Class 3

**COLORFASTNESS TO LIGHT**  
60 hours

## CLEANING

**WS: Water/Solvent Cleaner** - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

[Additional cleaning details at www.mayerfabrics.com](http://www.mayerfabrics.com)

