

ELEMENT FELDSPAR

316-003

MAYER FABRICS



CLEANING

WS: Water/Solvent Cleaner - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

[Additional cleaning details at www.mayerfabrics.com](http://www.mayerfabrics.com)

CATEGORY

Seating

PROPERTIES



CONTENT

85% Pre-Consumer Recycled Polyester/15% Polyester

ADDITIONAL FINISHING AVAILABLE (CHECK FOR PRICING)

NanoGuard

FINISH

INCASE(TM) with Antimicrobial Silver Ion Technology

WIDTH

54"

WEIGHT

13

SHOWN RAILROADED

No

DIRECTIONALITY

Yes

ROLL LENGTH

60 yards

VISUAL REPEAT

Non-Matching

BREAKING STRENGTH

Warp: 311.0 lbs. / Fill: 213.0 lbs.

SEAM SLIPPAGE

Warp: 86.0 lbs. / Fill: 75.0 lbs.

ABRASION RESISTANCE

Passes 130,000 Double Rubs (Wyzenbeek) *

* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

PILLING RESISTANCE

Class: 5

COLORFASTNESS TO CROCKING

Dry: Class 4 / Wet: Class 3.5

COLORFASTNESS TO LIGHT

60 hours