


# ELEMENT PUTTY

316-007

# MAYER FABRICS



**CATEGORY**  
Seating

**PROPERTIES**

**CONTENT**  
85% Pre-Consumer Recycled Polyester/15% Polyester

**ADDITIONAL FINISHING AVAILABLE  
(CHECK FOR PRICING)**  
NanoGuard

**FINISH**  
INCASE(TM) with Antimicrobial Silver Ion  
Technology

**WIDTH**  
54"

**WEIGHT**  
13

**SHOWN RAILROADED**  
No

**DIRECTIONALITY**  
Yes

**ROLL LENGTH**  
60 yards

**VISUAL REPEAT**  
Non-Matching

**BREAKING STRENGTH**  
Warp: 311.0 lbs. / Fill: 213.0 lbs.

**SEAM SLIPPAGE**  
Warp: 86.0 lbs. / Fill: 75.0 lbs.

**ABRASION RESISTANCE**  
Passes 130,000 Double Rubs (Wyzenbeek) \*  
\* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

**PILLING RESISTANCE**  
Class: 5

**COLORFASTNESS TO CROCKING**  
Dry: Class 4 / Wet: Class 3.5

**COLORFASTNESS TO LIGHT**  
60 hours

## CLEANING

**WS: Water/Solvent Cleaner** - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

[Additional cleaning details at www.mayerfabrics.com](http://www.mayerfabrics.com)