



CATEGORY

Seating

PROPERTIES



CONTENT

57% Cotton/43% Polyester

ADDITIONAL FINISHING AVAILABLE
(CHECK FOR PRICING)

Nano-Tex, NanoGuard

FINISH

Nanotex®

WIDTH

54"

WEIGHT

12.64

SHOWN RAILROADED

No

DIRECTIONALITY

Yes

ROLL LENGTH

60

VISUAL REPEAT

14.38, 13.25 Random Match

BREAKING STRENGTH

Warp: 100.0 lbs. / Fill: 75.0 lbs.

SEAM SLIPPAGE

Warp: 81.0 lbs. / Fill: 50.0 lbs.

ABRASION RESISTANCE

Passes 100,000 Double Rubs (Wyzenbeek) *

* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

PILLING RESISTANCE

Class: 3

COLORFASTNESS TO CROCKING

Dry: Class 4 / Wet: Class 3

COLORFASTNESS TO LIGHT

40 hours

CLEANING

S: Solvent Cleaner - Spot clean, using a mild water-free solvent or dry cleaning product. Clean only in a well-ventilated room and avoid any product containing carbon tetrachloride or other toxic materials. Pretest a small area before proceeding. Always rinse promptly with clean water.

[Additional cleaning details at www.mayerfabrics.com](http://www.mayerfabrics.com)