



CATEGORY  
Seating/Panel

PROPERTIES

CONTENT  
100% Recycled Polyester (60% Pre-/40% Post-Consumer)

ADDITIONAL FINISHING AVAILABLE  
(CHECK FOR PRICING)  
Nano-Tex, NanoGuard

FINISH  
None

WIDTH  
54"

WEIGHT  
7.8

SHOWN RAILROADED  
No

DIRECTIONALITY  
Yes

ROLL LENGTH  
60

VISUAL REPEAT  
1.2, 1.75

BREAKING STRENGTH  
Warp: 159.0 lbs. / Fill: 115.0 lbs.

SEAM SLIPPAGE  
Warp: 39.0 lbs. / Fill: 41.0 lbs.

ABRASION RESISTANCE  
Passes 60,000 Double Rubs (Wyzenbeek/Cotton Duck) \*  
\* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

PILLING RESISTANCE  
Class: 4

COLORFASTNESS TO CROCKING  
Dry: Class 4 / Wet: Class 4

COLORFASTNESS TO LIGHT  
40 hours

#### CLEANING

**WS: Water/Solvent Cleaner** - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

[Additional cleaning details at www.mayerfabrics.com](http://www.mayerfabrics.com)

