


ARTISTRY PARCHMENT

368-007

MAYER FABRICS



CLEANING

S: Solvent Cleaner - Spot clean, using a mild water-free solvent or dry cleaning product. Clean only in a well-ventilated room and avoid any product containing carbon tetrachloride or other toxic materials. Pretest a small area before proceeding. Always rinse promptly with clean water.

[Additional cleaning details at www.mayerfabrics.com](http://www.mayerfabrics.com)

CATEGORY

Seating

PROPERTIES



CONTENT

100% Polyester

ADDITIONAL FINISHING AVAILABLE (CHECK FOR PRICING)

Nano-Tex, NanoGuard

FINISH

Stain Repellent

WIDTH

54"

WEIGHT

10.8

SHOWN RAILROADED

No

DIRECTIONALITY

Yes

ROLL LENGTH

60

VISUAL REPEAT

3.5, 4.8

BREAKING STRENGTH

Warp: 249.0 lbs. / Fill: 258.0 lbs.

SEAM SLIPPAGE

Warp: 43.0 lbs. / Fill: 72.0 lbs.

ABRASION RESISTANCE

Passes 60,000 Double Rubs (Wyzenbeek/Cotton Duck) *

* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

PILLING RESISTANCE

Class: 5

COLORFASTNESS TO CROCKING

Dry: Class 4 min / Wet: Class 3 min

COLORFASTNESS TO LIGHT

40 hours