



#### CATEGORY

Seating/Panel

#### PROPERTIES



#### CONTENT

100% Recycled Polyester (65% Pre-/35% Post-Consumer)/65% Recycled Polyester/35% Recycled Polyester

#### ADDITIONAL FINISHING AVAILABLE (CHECK FOR PRICING)

Nano-TEX, NanoGuard

#### FINISH

None

#### WIDTH

54"

#### WEIGHT

10.69

#### SHOWN RAILROADED

No

#### DIRECTIONALITY

Yes

#### ROLL LENGTH

55

#### VISUAL REPEAT

15.0, 12.88 Non-Matching

#### BREAKING STRENGTH

Warp: 251.0 lbs. / Fill: 132.0 lbs.

#### SEAM SLIPPAGE

Warp: 35.0 lbs. / Fill: 77.0 lbs.

#### ABRASION RESISTANCE

Passes 51,000 Double Rubs (Wyzenbeek/Cotton Duck) \*

\* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

#### PILLING RESISTANCE

Class: 5

#### COLORFASTNESS TO CROCKING

Dry: Class 4 min / Wet: Class 3 min

#### COLORFASTNESS TO LIGHT

40 hours

#### CLEANING

**WS: Water/Solvent Cleaner** - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent.

When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

**BC: Bleach Cleanable** - 1 parts bleach, 9 parts water = 10% bleach, 90% water solution. Do not clean / disinfect fabric for longer than 10 minutes using the 10% bleach solution.

Always rinse promptly with clean water after applying the bleach solution. Failure to do so will void any and all warranties.

[Additional cleaning details at www.mayerfabrics.com](http://www.mayerfabrics.com)

