



CATEGORY  
Seating/Panel

PROPERTIES

CONTENT  
100% Recycled Polyester (65% Pre-/35% Post-Consumer)/65% Recycled Polyester/35% Recycled Polyester

ADDITIONAL FINISHING AVAILABLE  
(CHECK FOR PRICING)  
Nano-Tex, NanoGuard

FINISH  
None

WIDTH  
54"

WEIGHT  
10.69

SHOWN RAILROADED  
No

DIRECTIONALITY  
Yes

ROLL LENGTH  
55

VISUAL REPEAT  
15.0, 12.88 Non-Matching

BREAKING STRENGTH  
Warp: 251.0 lbs. / Fill: 132.0 lbs.

SEAM SLIPPAGE  
Warp: 35.0 lbs. / Fill: 77.0 lbs.

ABRASION RESISTANCE  
Passes 51,000 Double Rubs (Wyzenbeek/Cotton Duck) \*  
\* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

PILLING RESISTANCE  
Class: 5

COLORFASTNESS TO CROCKING  
Dry: Class 4 min / Wet: Class 3 min

COLORFASTNESS TO LIGHT  
40 hours

#### CLEANING

**WS: Water/Solvent Cleaner** - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

**BC: Bleach Cleanable** - 1 parts bleach, 9 parts water = 10% bleach, 90% water solution. Do not clean / disinfect fabric for longer than 10 minutes using the 10% bleach solution. Always rinse promptly with clean water after applying the bleach solution. Failure to do so will void any and all warranties.

[Additional cleaning details at www.mayerfabrics.com](http://www.mayerfabrics.com)

