



CATEGORY

Seating

PROPERTIES



CONTENT

43% Solution Dyed Pre-Consumer Recycled Nylon/43% Solution Dyed Nylon/12% Polyester/2% Olefin

ADDITIONAL FINISHING AVAILABLE (CHECK FOR PRICING)

Nano-Tex, NanoGuard

FINISH

Stain Repellent and Antimicrobial

WIDTH

54"

WEIGHT

16.5

SHOWN RAILROADED

No

DIRECTIONALITY

Yes

ROLL LENGTH

56 yards

VISUAL REPEAT

14.2, 7.1 Random Match

BREAKING STRENGTH

Warp: 225.0 lbs. / Fill: 150.0 lbs.

SEAM SLIPPAGE

Warp: 50.0 lbs. / Fill: 50.0 lbs.

ABRASION RESISTANCE

Passes 155,000 Double Rubs (Wyzenbeek) *

* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

PILLING RESISTANCE

Class: 4 min

COLORFASTNESS TO CROCKING

Dry: Class 4 min / Wet: Class 3 min

COLORFASTNESS TO LIGHT

200 hours

CLEANING

WS: Water/Solvent Cleaner - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent.

When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

BC: Bleach Cleanable - 1 parts bleach, 4 parts water = 20% bleach, 80% water solution. Do not clean / disinfect fabric for longer than 10 minutes using the 20% bleach solution. Always rinse promptly with clean water after applying the bleach solution. Failure to do so will void any and all warranties.

[Additional cleaning details at www.mayerfabrics.com](http://www.mayerfabrics.com)