MATRIX GREYSTONE



CLEANING

WS: Water/Solvent Cleaner - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

BC: Bleach Cleanable - 1 parts bleach, 4 parts water = 20% bleach, 80% water solution. Do not clean / disinfect fabric for longer than 10 minutes using the 20% bleach solution. Always rinse promptly with clean water after applying the bleach solution. Failure to do so will void any and all warranties.

Additional cleaning details at www.mayerfabrics.com

MAYER FABRICS

CATEGORY Seating

CONTENT

50% Solution Dyed Nylon/50% Solution Dyed Pre-Consumer Recycled Nylon

ADDITIONAL FINISHING AVAILABLE (CHECK FOR PRICING)

Nano-Tex, NanoGuard

FINISH Stain Repellent and Antimicrobial

WIDTH 54"

WEIGHT

14.5

SHOWN RAILROADED No

DIRECTIONALITY Yes

ROLL LENGTH 56 yards

VISUAL REPEAT 7.1, 14.625 Random Match

BREAKING STRENGTH Warp: 250.0 lbs. / Fill: 300.0 lbs.

SEAM SLIPPAGE Warp: 50.0 lbs. / Fill: 50.0 lbs.

ABRASION RESISTANCE Passes 305,000 Double Rubs (Wyzenbeek) * * Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

PILLING RESISTANCE Class: 4 min

COLORFASTNESS TO CROCKING Dry: Class 4 min / Wet: Class 3 min

COLORFASTNESS TO LIGHT 200 hours