

WILDFLOWER SANDSTONE

392-019

MAYER FABRICS



CATEGORY

Seating

PROPERTIES



CONTENT

90% Repreve Solution Dyed Pre-Consumer Recycled Nylon/7% Solution Dyed Pre-Consumer Recycled Nylon/3% Solution Dyed Post-Consumer Recycled Nylon

FINISH

Stain Repellent

WIDTH

54"

WEIGHT

13.79

SHOWN RAILROADED

No

DIRECTIONALITY

Yes

ROLL LENGTH

~55-60 yards

VISUAL REPEAT

14.375, 19.0

BREAKING STRENGTH

Warp: 213.0 lbs. / Fill: 342.0 lbs.

SEAM SLIPPAGE

Warp: 78.0 lbs. / Fill: 96.0 lbs.

ABRASION RESISTANCE

Passes 165,000 Double Rubs (Wyzenbeek) *

* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

PILLING RESISTANCE

Class: 5

COLORFASTNESS TO CROCKING

Dry: Class 4 / Wet: Class 3

COLORFASTNESS TO LIGHT

240 hours

CLEANING

WS: Water/Solvent Cleaner - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent.

When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

BC: Bleach Cleanable - 1 parts bleach, 4 parts water = 20% bleach, 80% water solution. Do not clean / disinfect fabric for longer than 10 minutes using the 20% bleach solution. Always rinse promptly with clean water after applying the bleach solution. Failure to do so will void any and all warranties.

[Additional cleaning details at www.mayerfabrics.com](http://www.mayerfabrics.com)



© Mayer Fabrics 2024

Specifications are subject to change. Current specifications are available at mayerfabrics.com
Mayer Fabrics | 500 S. Kitley Ave, Indianapolis, IN 46219

TF. 800.428.4415
T. 317.267.2626
F. 317.267.2629