

PUNO SPRING

444-002

MAYER FABRICS



CATEGORY
Seating

PROPERTIES

CONTENT
98% Sunbrella® Acrylic/2% Sunbrella® Polyester

FINISH
Liquid and Stain Repel - PFOA & PFOS Free

WIDTH
54"

WEIGHT
16.72

SHOWN RAILOADED
Yes

DIRECTIONALITY
Yes

ROLL LENGTH
50 yards

VISUAL REPEAT
7.39,

BREAKING STRENGTH
Warp: 228.0 lbs. / Fill: 344.0 lbs.

SEAM SLIPPAGE
Warp: 101.0 lbs. / Fill: 97.0 lbs.

ABRASION RESISTANCE
Exceeds 100,000 Double Rubs (Wyzenbeek) *
* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

PILLING RESISTANCE
Class: 5

COLORFASTNESS TO CROCKING
Dry: Class 4 min / Wet: Class 4 min

COLORFASTNESS TO LIGHT
2000 hours

APPLICATION
Atrium, Indoor, Outdoor

CLEANING

WS: Water/Solvent Cleaner - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

BC: Bleach Cleanable - 1 parts bleach, 9 parts water = 10% bleach, 90% water solution. Do not clean / disinfect fabric for longer than 10 minutes using the 10% bleach solution. Always rinse promptly with clean water after applying the bleach solution. Failure to do so will void any and all warranties.

[Additional cleaning details at www.mayerfabrics.com](http://www.mayerfabrics.com)



© Mayer Fabrics 2024

Specifications are subject to change. Current specifications are available at mayerfabrics.com
Mayer Fabrics | 500 S. Kitley Ave, Indianapolis, IN 46219

TF. 800.428.4415
T. 317.267.2626
F. 317.267.2629