ELEVATION INDIGO





CATEGORY Seating

PROPERTIES



CONTENT

100% Post-Consumer Recycled Polyester

ADDITIONAL FINISHING AVAILABLE (CHECK FOR PRICING)

Nano-Tex, NanoGuard

FINISH

Stain Repellent - PFOA & PFOS Free

WIDTH

54"

WEIGHT

15.8

SHOWN RAILROADED

No

DIRECTIONALITY

Nο

ROLL LENGTH

55 yards

VISUAL REPEAT

14.25, 13.25 Non-Matching

BREAKING STRENGTH

Warp: 233.0 lbs. / Fill: 273.0 lbs.

SEAM SLIPPAGE

Warp: 65.0 lbs. / Fill: 60.0 lbs.

ABRASION RESISTANCE

Passes 80,000 Double Rubs (Wyzenbeek) *

* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

PILLING RESISTANCE

Class: 4 min

COLORFASTNESS TO CROCKING

Dry: Class 4 min / Wet: Class 3 min

COLORFASTNESS TO LIGHT

40 hours

CLEANING

WS: Water/Solvent Cleaner - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

BC: Bleach Cleanable - 1 parts bleach, 9 parts water = 10% bleach, 90% water solution. Do not clean / disinfect fabric for longer than 10 minutes using the 10% bleach solution. Always rinse promptly with clean water after applying the bleach solution. Failure to do so will void any and all warranties.

Additional cleaning details at www.mayerfabrics.com