

# VIBRANT PARCHMENT

833-007

# MAYER FABRICS



## CLEANING

**S: Solvent Cleaner** - Spot clean, using a mild water-free solvent or dry cleaning product. Clean only in a well-ventilated room and avoid any product containing carbon tetrachloride or other toxic materials. Pretest a small area before proceeding. Always rinse promptly with clean water.

[Additional cleaning details at www.mayerfabrics.com](http://www.mayerfabrics.com)

## CATEGORY

Seating

## PROPERTIES



## CONTENT

66% Recycled Polyester (38% Pre-/28% Post-Consumer)/38% Recycled Polyester/34% Cotton/28% Recycled Polyester

## ADDITIONAL FINISHING AVAILABLE (CHECK FOR PRICING)

Nano-Tex, NanoGuard

## FINISH

None

## WIDTH

54"

## WEIGHT

14.72

## SHOWN RAILROADED

No

## DIRECTIONALITY

Yes

## ROLL LENGTH

55

## VISUAL REPEAT

1.25, 1.0

## BREAKING STRENGTH

Warp: 215.0 lbs. / Fill: 138.0 lbs.

## SEAM SLIPPAGE

Warp: 52.0 lbs. / Fill: 60.0 lbs.

## ABRASION RESISTANCE

Passes 51,000 Double Rubs (Wyzenbeek/Cotton Duck) \*

\* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

## PILLING RESISTANCE

Class: 5

## COLORFASTNESS TO CROCKING

Dry: Class 4 min / Wet: Class 3 min

## COLORFASTNESS TO LIGHT

40 hours