JUNCTURE LIMELIGHT
890-003

MAYER FABRICS



CLEANING
S: Solvent Cleaner - Spot clean, using a mild water-free solvent or dry cleaning product. Clean only in a well-ventilated room and avoid any product containing carbon tetrachloride or other toxic materials. Pretest a small area before proceeding. Always rinse promptly with clean water.

Additional cleaning details at www.mayerfabrics.com

CATEGORY
Seating

PROPERTIES

CONTENT
75% Cotton/25% Nylon

FINISH
INCASE(TM) with Antimicrobial Silver Ion Technology

WIDTH
54"

WEIGHT
20.48

SHOWN RAILROADED
No

DIRECTIONALITY
Yes

ROLL LENGTH
60 yards

VISUAL REPEAT
13.5, 13.0

BREAKING STRENGTH
Warp: 328.0 lbs. / Fill: 269.0 lbs.

SEAM SLIPPAGE
Warp: 77.0 lbs. / Fill: 105.0 lbs.

ABRASION RESISTANCE
Exceeds 100,000 Double Rubs (Wyzenbeek) *
* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

PILLING RESISTANCE
Class: 3

COLORFASTNESS TO CROCKING
Dry: Class 4 min / Wet: Class 4 min

COLORFASTNESS TO LIGHT
60 hours

INCASE CRYPTON® TECHNOLOGY

© Mayer Fabrics 2024

Specifications are subject to change. Current specifications are available at mayerfabrics.com

Mayer Fabrics | 500 S. Kitley Ave, Indianapolis, IN 46219

TF. 800.428.4415
T. 317.267.2626
F. 317.267.2629