BERKSHIRE SABLE



CLEANING

WS: Water/Solvent Cleaner - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

CFC: Coated Fabrics Cleaning - When a spill/stain occurs wipe immediately with a clean dry cloth. Carefully remove the majority of the stain then follow the steps below.

Soap & Water - Remove ordinary dirt and smudges with a mild soap and water solution using a soft cloth or towel. Rinse with fresh water and wipe dry.

Non-abrasive Cleaners - If residue remains, use a straight application of the following cleaners: Fantastik or 409 and gently clean with a soft cloth. Rinse with fresh water and wipe dry. Isopropyl Alcohol - More stubborn stains may be eliminated using a cotton cloth soaked in 70-91% isopropyl (rubbing) alcohol. Wipe without spreading stain to surrounding area. A second application should be applied with vigorous rubbing in a circular motion. For highly textured material, a soft brush is recommended to clean valleys and crevices. Rinse with fresh water and wipe dry.

BC: Bleach Cleanable - 1 parts bleach, 4 parts water = 20% bleach, 80% water solution. Do not clean / disinfect fabric for longer than 10 minutes using the 20% bleach solution. Always rinse promptly with clean water after applying the bleach solution. Failure to do so will void any and all warranties.

Write-Away products from Mayer Fabrics defies unsightly ink spots and paint stains. Take action 'right away' on Write-Away products by following the cleaning instructions for Ink Stains. Always rinse specifications are available at mayerfabrics.com Mayer Fabrics | 500 S. Kitley Ave, Indianapolis, IN 46219 Additional cleaning details at www.mayerfabrics.com



CATEGORY Seating

CONTENT

62% Polyurethane Polycarbonate - PVC Free face, 38% Polyester backing

FINISH

WRITE AWAY® - Soil & Stain Resistant Top Coat with Ink Resistant Technology

WIDTH

54"

No

WEIGHT 20

SHOWN RAILROADED

DIRECTIONALITY

Yes

ROLL LENGTH 30 yards

VISUAL REPEAT Non-Matching

BREAKING STRENGTH Warp: 144.0 lbs. / Fill: 113.0 lbs.

SEAM SLIPPAGE Warp: 60.0 lbs. / Fill: 44.0 lbs.

ABRASION RESISTANCE Exceeds 250,000 Double Rubs (Wyzenbeek) * * Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

PILLING RESISTANCE Class: n/a

COLORFASTNESS TO CROCKING Dry: Class 4 min / Wet: Class 4 min

COLORFASTNESS TO LIGHT 200 hours