# BLOCKS SEASHORE

# 



## CLEANING

**WS: Water/Solvent Cleaner** - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

**CFC:** Coated Fabrics Cleaning - When a spill/stain occurs wipe immediately with a clean dry cloth. Carefully remove the majority of the stain then follow the steps below.

Soap & Water - Remove ordinary dirt and smudges with a mild soap and water solution using a soft cloth or towel. Rinse with fresh water and wipe dry.

Non-abrasive Cleaners - If residue remains, use a straight application of the following cleaners: Fantastik or 409 and gently clean with a soft cloth. Rinse with fresh water and wipe dry. Isopropyl Alcohol - More stubborn stains may be eliminated using a cotton cloth soaked in 70-91% isopropyl (rubbing) alcohol. Wipe without spreading stain to surrounding area. A second application should be applied with vigorous rubbing in a circular motion. For highly textured material, a soft brush is recommended to clean valleys and crevices. Rinse with fresh water and wipe dry.

**BC: Bleach Cleanable** - 1 parts bleach, 10 parts water = 9% bleach, **Prefixe** t clean / disinfect fabric for longer than 10 Che solution. Always rinse promptly with the bleach solution. Failure to do so will

#### Additional cleaning details at www.mayerfabrics.com

© Mayer Fabrics 2024

Specifications are subject to change. Current specifications are available at mayerfabrics.com Mayer Fabrics | 500 S. Kitley Ave, Indianapolis, IN 46219



CATEGORY Seating

## PROPERTIES ₩₩₩★★

CONTENT 100% Vinyl

#### FINISH

Soil & Stain Resistant Top Coat with Ink Resistant Technology

WIDTH 54"

WEIGHT 28

SHOWN RAILROADED

DIRECTIONALITY

Yes

No

ROLL LENGTH 30 yards

VISUAL REPEAT 9.25, 8.5 Random Match

BREAKING STRENGTH Warp: 85.0 lbs. / Fill: 75.0 lbs.

SEAM SLIPPAGE Warp: lbs. / Fill: lbs.

ABRASION RESISTANCE Passes 1,300,000 Double Rubs (Wyzenbeek) \* \* Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan.

PILLING RESISTANCE Class: N/A

COLORFASTNESS TO CROCKING Dry: Class 4 min / Wet: Class 4 min

COLORFASTNESS TO LIGHT 650 hours

APPLICATION Atrium, Indoor, Marine, Outdoor

> TF. 800.428.4415 T. 317.267.2626 F. 317.267.2629