

# CARESSA FR

---

Faux Leather




**MAYER**FABRICS


# Faux Leather




CA-051 Paprika



CA-029 Ochre



CA-019 Bittersweet




CA-009 Red Clay




CA-031 Brick



CA-011 Lipstick




CA-021 Red Pepper




CA-001 Ruby




CA-041 Burgundy




CA-005 Aubergine



CA-015 Lavendar



CA-024 Iris




CA-004 Navy




CA-074 Spa




CA-064 Cerulean



CA-044 Cadet




CA-014 Admiral



CA-084 Aqua



CA-093 Bluegrass



CA-003 Orchard



CA-023 Spruce

**Use**  
Seating

**Content**  
100% Vinyl


**Width**  
54 inches

**Abrasion**  
Exceeds 650,000 Double Rubs


**Finish**  
Resilience<sup>SR</sup>



CA-063 Willow




CA-053 Laurel



CA-083 Wasabi




CA-073 Basil




CA-022 Banana



CA-002 Butterscotch



CA-057 Bisque



CA-067 Ecrú



CA-027 Buff



CA-012 Mojave




CA-050 Saddle



CA-020 Jersey



CA-060 Caramel




CA-070 Rawhide




CA-000 Coco



CA-040 Java




CA-047 Doe



CA-037 Papyrus




CA-030 Taupe




CA-010 Chocolate



CA-077 Ivory




CA-007 Kilimanjaro



CA-046 Stone




CA-026 Granite




CA-056 White



CA-066 Zinc



CA-016 Pewter



CA-006 Black

## TECHNICAL INFORMATION

Content: 100% Vinyl Width: 54" Weight: 29 oz./linear yd	Backing: 100% Brushed Polyester Knit Finish: ResilienceSR Cleaning Code: WS	Visual Repeat: None Directional: No Railroaded: No
<b>PERFORMANCE</b> (*ACT® Registered Certification Marks)	Test Method	Results
Surface Abrasion: Heavy Duty <b>A</b>	ASTM D 3597/4157 (Cotton Duck)	Exceeds 650,000 Double Rubs
Breaking Strength:	CFFA-17 / ASTM D751	Warp 142 lbs. / Fill 97 lbs.
Seam Slippage:	CFFA-14 / Method ASTM D751	Warp 58 lbs. / Fill 41 lbs.
Colorfastness to Crocking:	AATCC 8	Dry: Class 4 min. / Wet: Class 4 min.
Colorfastness to Light:	UV Resistance G154-06	500 Hours - Suitable for Marine Use
Cold Crack:	CFFA-6 Fed. Stnd. No. 191A - Method 5874	-20° F

## FLAMMABILITY

California Technical Bulletin 117, Section E	Passes
NFPA 260 (Equivalent to UFAC) Class 1	Passes
ASTM E84 (Adhered) Class 1 or A	Passes
BIFMA CS-191-53, Section 3	Passes
BIFMA Upholstery, Section 4	Passes
Boston Fire Dept. Code (BFD IX-1)	Passes
FMVSS 302	Passes
IMO A.652 (16) 8.2 & 8.3	Passes
NY & NJ Port Authority	Passes

Should comply with California Technical Bulletin 133 when combined with appropriate components.

## SPECIFIC TREATMENTS

Resilience<sup>SR</sup> Stain Resistant Abrasion Resistant Anti-Bacterial Anti-Microbial Sulfide Stain Resistant Mildew Resistant Bleach Resistant (diluted 1:10)

## STAIN RESISTANCE

Stain Resistance per CFFA 141 - Class 5 (Excellent) rating:

Ketchup	Mayonnaise	Soy Sauce	Butter	Tea	Whiskey	Coffee	Soda
Blood	Urine	Iodine/Betandine	Mascara	Hair Spray	Suntan Lotion	Lipstick	Motor Oil

## Resilience<sup>SR</sup>

**ENDURING PROTECTION** Resilience<sup>SR</sup> represents the latest technology in Faux Leather and Vinyl Protection, enhancing performance where it is needed the most.

**Stain Resistance:** With proper care, materials treated with Resilience<sup>SR</sup> can be easily cleaned and will guard against stains maintaining the desired surface appearance for years to come.

**Anti-Microbial & Anti-Bacterial Protection:** Products treated with Resilience<sup>SR</sup> are engineered to inhibit bacterial growth, as well as fungus, mold and mildew spores, resulting in a more hygienic environment.

**Abrasion Resistance:** Resilience<sup>SR</sup> provides additional wear properties and surface durability to any Vinyl or Faux Leather, thereby increasing the life of the material.

Resilience<sup>SR</sup> is not visible, and does not affect the hand of the material. Resilience<sup>SR</sup> is engineered to last, even after repeated cleaning and wear. Specify Resilience<sup>SR</sup> for the most demanding healthcare and hospitality applications.

## CLEANING INFORMATION

WS: Water/Solvent Cleaner - Spot clean, with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding.

Bleach Resistant (diluted 1:10)

Prompt cleaning is always recommended. Recommended cleaning steps are listed by type of stain.

## ADDITIONAL INFORMATION

**Custom Capabilities:** All patterns can be custom colored. Minimum yardage applies.

**Memo Samples:** Please keep this card intact. Individual memo samples can be ordered on our web site or by contacting customer service.

**Color Matching:** Mayer Fabrics always attempts to ship a satisfactory commercial match. Because of industry standard dye lot variation, colors may not match exactly.

**Specifications:** Specifications are correct at the time of printing. Current specifications are available on our web site.

For information or assistance with products or services, call us at 800.428.4415 or refer to our web site, [www.mayerfabrics.com](http://www.mayerfabrics.com).



**MAYERFABRICS**

**GSA Contract #GS-28F-0022P**