officemaster

Fabric Catalog

Stage 3V50-3V59



Specifications:

Content: 100% Vinyl/Urethane Topcoat Backing: 100% Polyester Hi-Loft (TM)

Width: 54"

3V58 Shrek

Finish: SILVERGUARD (R) & PERMABLOK3 (R)

3V59 Fame

Abrasion: 930,000 Double Rubs Breaking Strength: Warp 70.0 lbs. Lightfastness: Passes 1000 Hours

Flammability: Passes California TB 117-2013; NFPA 260 (Equivalent to UFAC) Class1; Boston Fire Dept. Code (BFD 1X-1); FAA/FAR 25.853 (a); Fed. Stnd. 191A Test Method 5903.1 - Vertical Flammability Test; FMVSS 302; IMO A. 652(16) 8.2 & 8.3; NFPA 701 (sma

Cleaning Code: WS

Fabric Disclaimer:

Monitors and display settings vary widely between computers. As a result, all fabric colors shown here are approximate and subject to variance from the actual color on physical chairs. For more accurate ideas of color tones, etc. please contact your favorite Office Master representative to obtain a sample or fabric swatch.

Please visit http://OfficeMaster.com for more information

Office Master Inc.

1110 South Mildred Avenue Ontario, California 91761

toll free: (877) 776-5678 phone: (909) 392-5678 fax: (909) 392-4567

email: om@officemaster.com